

RS 94 Steel Rectangular Backboard:

SUPPLY & INSTALL:

RS 94 – Steel Rectangular Backboard

48" (1220 mm) x 72" (1829 mm) x steel backboard with baked on powder coat finish.

Recommended goal for this unit is **RS F/M** or **RS 2000 Breakaway Goal**.

The RS 94 backboard shall be formed from a single piece of heavy gauge steel and reinforced with a heavy 10-gauge vertical center channel and heavy gauge horizontal channels. All reinforcing sections shall be welded to the shell to make a single vibration free unit. Manufacturer of backboard shall have over ten years experience producing such item. Key-slots in the horizontal channels shall be spaced at 20" vertical and 35" horizontal. Backboard shall be phosphate pre-treated and shall have a durable white powder coat finish to protect against weathering. Optional orange border and target shall be silk-screened on face of backboard for permanent markings. Please specify at time of ordering if border & target are required. Goal mounting holes shall be on 5" horizontal and 5" vertical centers.

12 GA STEEL STAMPED SHELL WITH 12 GA. FORMED MOUNTING AND STIFFENING CHANNELS WELDED TO REVERSE SIDE.

BOARD THICKNESS IS 1 1/2".

MOUNTING HOLES FOR 3/8" DIAMETER GOAL AND BOARD MOUNTING HARDWARE.

BOARD IS POWDER COATED GLOSS WHITE.

